



# SUPER PLUS ROTAVATOR

High-quality, cutting-edge, robust & Economic Implements

PREMIUM QUALITY

BEST PRICE

Trusted and Durable

Best for both medium and hard soil combined features of **LIGHT** and **SMART**  
All type of Rotavator available



Also available in "J" type blades

SCAN ME  
WATCH DEMO VIDEOS



Size Available / Tractor Power (HP)

| Feet | 3     | 4     | 5     | 5.5   | 6     | 7     |
|------|-------|-------|-------|-------|-------|-------|
| HP   | 30-45 | 35-50 | 40-55 | 45-60 | 50-65 | 55-65 |

SAVES TIME, MONEY AND GENERATES MORE INCOME



## SUPER PLUS : TECHNICAL SPECIFICATIONS

| MODEL/FEET                    | ASRT-3 FT SUPER PLUS | ASRT-4 FT SUPER PLUS | ASRT-5 FT SUPER PLUS | ASRT-5.5 FT SUPER PLUS | ASRT-6 FT SUPER PLUS | ASRT-7 FT SUPER PLUS |
|-------------------------------|----------------------|----------------------|----------------------|------------------------|----------------------|----------------------|
| Overall length (mm)           | 1212                 | 1414                 | 1760                 | 1889                   | 2026                 | 2259                 |
| overall width (mm)            | 812                  |                      |                      |                        |                      |                      |
| Overall Height (mm)           | 1135                 |                      |                      |                        |                      |                      |
| Tilling Width (mm)            | 1067                 | 1264                 | 1610                 | 1740                   | 1880                 | 2114                 |
| Tractor power (HP)            | 30-45                | 35-50                | 40-55                | 45-60                  | 50-65                | 55-65                |
| Tractor power (KW)            | 22-33                | 26-37                | 30-41                | 34-45                  | 37-48                | 41-48                |
| 3-Point Hitch type (KW)       | Cat-II               |                      |                      |                        |                      |                      |
| Frame Off-set (mm/inch)       | 33                   | 0                    | 0                    | 30                     | 0                    | 27                   |
| No. of Blade (L-80*7)         | 24                   | 30                   | 36                   | 39                     | 42                   | 48                   |
| No. of Blade (L-70*7)         | 30                   | 36                   | 42                   | 48                     | 54                   | 60                   |
| Standard Tyne Construction    | Square /Curve        |                      |                      |                        |                      |                      |
| Transmission Type             | Gear Drive           |                      |                      |                        |                      |                      |
| Max. Working Depth(mm/inch)   | 203/8                |                      |                      |                        |                      |                      |
| Rotor Tube Diameter(mm/inch)  | 89/3                 |                      |                      |                        |                      |                      |
| Rotor Swing Diameter(mm/inch) | 480                  |                      |                      |                        |                      |                      |
| Drive line Safety Device      | Shear Bolt           |                      |                      |                        |                      |                      |
| Weight (KG)                   | 345                  | 375                  | 410                  | 430                    | 445                  | 480                  |

### ROTOR RPM CHART

| SERIES                    | INPUT RPM | GEAR BOX | SPUR GEAR -1 | SPUR GEAR -2 | ROTOR SPEED |
|---------------------------|-----------|----------|--------------|--------------|-------------|
| SUPER PLUS GD             | 540       | S.S.     | -            | -            | 235         |
|                           |           |          | 16           | 20           | 160         |
|                           |           |          | 17           | 19           | 179         |
|                           | 1000      | M.S.     | 19           | 17           | 224         |
|                           |           |          | 20           | 16           | 250         |
|                           |           |          | 15           | 21           | 265         |
|                           |           |          | 17           | 27           | 233         |
| CROWN                     | 25        |          |              |              |             |
| PINION                    | 13        |          |              |              |             |
| SIDE GEAR                 | 20-35-28  |          |              |              |             |
| SINGLE SPEED CROWN-PINION | 11-18     |          |              |              |             |



### SALIENT FEATURES



Heavy Duty Gearbox



Powder Coated Paint



Boron Steel Blades



Mechanical (Duo cone) Oil Seal



Strong Body Frame



Flexible Spring Assembly



High Quality Spare Parts



High Tensile Fasteners

#### NOTE :

- \* Weight is excluding PTO.
- \* Accessories shown are not part of standard equipment.
- \* The company reserves absolute rights to modify the specification of machine components therein without any prior notice.



**SUITABLE FOR  
ALL KIND OF CROPS**



#### AC AGRO TECHNOLOGY

Servey No. 288, Ranjitgadh, Nr. Wellsun Polymers,  
Maliya Highway, Halvad, Dist: Morbi, Gujarat - 363330.  
Email : [marketing@ashwashaktiagro.com](mailto:marketing@ashwashaktiagro.com)  
Web : [www.ashwashaktiagro.com](http://www.ashwashaktiagro.com)  
Contact : +91 98794 20340

Auth. Dealer



Leader in performance

Emerging Brand of Agricultural Implements