



HD PLUS PRO ROTAVATOR

High-quality,
cutting-edge,
robust & Economic
Implements

PREMIUM
QUALITY

BEST
PRICE

Trusted
and Durable

Made Exclusively for hard soil,
Helps in retaining moisture of the soil,
Increases soil porosity and aeration

All type of Rotavator available



SCAN ME
WATCH DEMO VIDEOS



Size Available / Tractor Power (HP)

Feet	4	5	5.5	6	7	8
HP	35-50	40-55	45-60	50-65	55-65	65-80

SAVES TIME, MONEY AND
GENERATES MORE INCOME



HD PLUS PRO : TECHNICAL SPECIFICATIONS

MODEL/FEET	ASRT-4 FT HD PLUS PRO	ASRT-5 FT HD PLUS PRO	ASRT-5.5 FT HD PLUS PRO	ASRT-6 FT HD PLUS PRO	ASRT-7 FT HD PLUS PRO	ASRT-8 FT HD PLUS PRO
Overall length (mm)	1414	1760	1880	2026	2259	2481
overall width (mm)	959					
Overall Height (mm)	1135					
Tilling Width (mm)	1150	1505	1640	1775	1945	2207
Tractor power (HP)	35-50	40-55	45-60	50-65	55-65	65-80
Tractor power (KW)	26-37	30-41	34-45	37-48	41-48	48-60
3-Point Hitch type	Cat-II					
Frame Off-set (mm/inch)	31	33	0	11	31	27
No. of Blade (L-80*7)	30	36	39	42	48	54
Standard Tyne Construction	Square /Curve					
Transmission Type	Gear Drive					
Max. Working Depth (mm/inch)	203/8					
Rotor Tube Diameter (mm/inch)	89/3					
Rotor Swing Diameter (mm/inch)	480					
Driveline Safety Device	Shear Bolt					
Weight (KG)	400	420	445	460	514	535

ROTOR RPM CHART

SERIES	INPUT RPM	GEAR BOX	SPUR GEAR -1	SPUR GEAR -2	ROTOR SPEED
HD PLUS PRO GD	540	S.S.	-	-	218
			16	19	183
		M.S.	17	18	205
			18	17	231
			19	16	258
	1000	M.S.	13	22	238
CROWN	23				
PINION	13				
SIDE GEAR	20-35-28				




SALIENT FEATURES



Heavy Duty Gearbox



Powder Coated Paint



Boron Steel Blades



Mechanical (Duo cone)
Oil Seal



Strong Body Frame



Flexible Spring Assembly



High Quality Spare Parts



High Tensile Fasteners

NOTE :

- * Weight is excluding PTO.
- * Accessories shown are not part of standard equipment.
- * The company reserves absolute rights to modify the specification of machine components therein without any prior notice.



**SUITABLE FOR
ALL KIND OF CROPS**



AC AGRO TECHNOLOGY

Servey No. 288, Ranjitgadh, Nr. Wellsun Polymers,
Maliya Highway, Halvad, Dist: Morbi, Gujarat - 363330.
Email : marketing@ashwashaktiagro.com
Web : www.ashwashaktiagro.com
Contact : +91 98794 20340

Auth. Dealer



Leader in performance

Emerging Brand of Agricultural Implements